


TEST PRESSURE: 4750 KPA  
WORKING PRESSURE: 3500 KPA

WORKING TEMPERATURES:  
WATER: EPDM 130° MAX.  
GAS: NITRILE OR NEOPRENE 95° MAX.  
STEAM/HYDROCARBONS:  
VITON 204°MAX.

MATERIALS:  
ARSENICAL BRASS CONFORMS  
WITH AS2345.  
ALTERNATIVELY  
ALL 316 STAINLESS STEEL METAL  
COMPONENTS.

ITEM 1A - EPDM  
ITEM 1B - NITRILE  
ITEM 1C - VITON



			ALL DIMENSIONS IN MILLIMETERS	TOLERANCES 0 - 300 = ±0.5mm ABOVE 300 - 1000 = ±1.0mm	SCALE 1 : 2	TITLE DN8 TEST PLUG BRASS & STAINLESS STEEL -MARKETING-		
			THIS DRAWING AND THE INFORMATION CONTAINED THEREIN IS THE PROPERTY OF COP-A-MATE PRODUCTS PTY. LTD. - AUSTRALIA. THIS DRAWING AND THE INFORMATION CONTAINED THEREIN IS CONFIDENTIAL INFORMATION WHICH ONLY MAY BE DISCLOSED ON A CONFIDENTIAL BASIS TO PERSONS DULY AUTHORISED BY THE OWNER. NO REPRODUCTION OF THIS DRAWING OR ANY OF THE INFORMATION CONTAINED THEREIN MAY BE MADE WITHOUT THE PRIOR EXPRESS PERMISSION OF THE OWNER, COP-A-MATE PRODUCTS PTY. LTD.		MATERIAL		DRG. No. 0023	
					DRN. CAM	DATE 17/11/97		SHEET 1
					CHKD	DATE		
No.	CHANGE	DATE	BY	COP-A-MATE PRODUCTS PTY LTD ACN No 091 031 677	BREAK AND DEBUR ALL SHARP EDGES AND CONERS			
REVISIONS								